



# COLD PATCH (CLASS 5)

## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

<b>Product identifier</b>	Cold Patch (Class 5)
Chemical Name	Mixture
CAS No.	Mixture
Trade Name(s)	Cold Patch Asphalt / Asphalt Repair Mix / Cold Mix Asphalt Pavement
<b>Relevant identified uses of the substance or mixture and uses advised against</b>	
Identified Use(s)	Asphalt Pavement Repair
Uses Advised Against	None.
<b>Details of the supplier of the safety data sheet</b>	
Company Identification	O&G Industries 112 Wall Street Torrington, Connecticut 06790
Telephone	(860) 489-9261
<b>Emergency telephone number</b>	
Emergency Phone No.	Not classified as dangerous for supply/use. Please contact the supplier above during normal business hours.

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200) / GHS Classification Skin Irrit. 2; Carc. 1B; STOT RE 2

#### Label elements

Hazard Symbol



**DANGER**

Signal Word(s)

Hazard Statement(s)

Causes skin irritation.  
May cause cancer.  
May cause damage to organs through prolonged or repeated exposure: blood, thymus, liver, spleen, bone marrow.

Precautionary Statement(s)

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Wash hands and exposed skin after use.



## COLD PATCH (CLASS 5)

### Other hazards

May cause eye irritation. May cause respiratory irritation.  
Prolonged exposure to fumes without adequate ventilation to fumes may cause upper respiratory irritation (nose & throat) .  
Skin contact may increase susceptibility to sunburn.  
Poisonous hydrogen sulfide gas can accumulate in the head-space of containers of certain asphalt products.  
Mechanical disruption (e.g., milling, cutting, chipping) of cured asphalt pavement may release crystalline silica dust from the aggregate.

### Additional Information

Avoid prolonged exposure to (dust/fume/gas/mist/vapors/spray) without adequate ventilation.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition/information on ingredients	% wt.	CAS No.
Aggregate (crushed stone, sand, gravel, slag)	80 - 95	Various
Petroleum asphalt / bitumen <sup>^</sup>	3 - 6	8052-42-4
Petroleum distillates (light & heavy hydrocracked, naphthenic, and cycle oils) <sup>**</sup>	1 - 5	Various

<sup>^</sup>Contains: <0.05% of 3 - 7 ring Polycyclic Aromatic Hydrocarbons (PAHs).

<sup>\*\*</sup>Contains: <0.2% benzene (CAS No. 71-43-2).

Other Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below. Please see Section 8 of SDS for more details.

- Contains: <0.1% airborne crystalline silica (inherent in aggregate) and <0.1% hydrogen sulfide.
- Hydrogen sulfide gas can accumulate in the head space of containers of certain asphalt products.
- Heated product releases asphalt fume.

Additional Information - None

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Inhalation	Not normally required. Move person to fresh air. Apply artificial respiration if necessary. If symptoms persist, obtain medical attention.
Skin Contact	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Eye Contact	Flush eyes with water for at least 15 minutes while holding eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention.
Ingestion	Not normally required. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### Most important symptoms and effects, both acute and delayed

None known



# COLD PATCH (CLASS 5)

**Indication of any immediate medical attention and special treatment needed**      None known

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

-Suitable Extinguishing Media      Extinguish with carbon dioxide, dry chemical, foam or water spray.  
 -Unsuitable Extinguishing Media      None anticipated.

### Special hazards arising from the substance or mixture

Combustion causes toxic fumes. Combustion products: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Sulfur oxides

### Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

### Environmental precautions

Not normally required.

### Methods and material for containment and cleaning up

Allow product to cool/solidify and pick up as a solid.

### Reference to other sections

None

### Additional Information

None.

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling

Avoid contact with skin and eyes.

### Conditions for safe storage, including any incompatibilities

-Storage temperature      Store at temperatures not exceeding the product's flash point.  
 -Incompatible materials      Strong oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA) *	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Asphalt fume	-----	-----	0.5 mg/m3 <sup>(1)</sup>	-----	-----	See below
Benzene	71-43-2	1 ppm *	0.5 ppm	5 ppm	2.5 ppm	Skin
Crystalline Silica (respirable particulate)	-----	0.050 mg/m3 <sup>(R)</sup> *	0.025 mg/m3 <sup>^</sup>	-----	-----	See below
Hydrogen sulfide	7783-06-4	-----	1 ppm	20 ppm ceiling	5 ppm	50 ppm peak

<sup>(1)</sup> Inhalable benzene-soluble fraction; <sup>(R)</sup>Respirable fraction; <sup>^</sup>Suspected Human Carcinogen; \* OSHA Carcinogen - employers must ensure compliance with OSHA 29 CFR 1926.1128 - Benzene and 1926.1153 - Respirable Crystalline Silica, as applicable.; TWA = 8 hour time-weighted average; STEL = Short Term Exposure Limit.



## COLD PATCH (CLASS 5)

### Recommended monitoring method

NIOSH 5042 (Asphalt Fume), OSHA Method 1005 (Benzene), OSHA ID-142 (Crystalline Silica), Electrochemical sensor (hydrogen sulfide).

### Exposure controls

#### Appropriate engineering controls

Use only outdoors or in a well-ventilated area.

#### Personal protection equipment

Eye/face protection



The following to be used as necessary: Safety Glasses

Skin protection (Hand protection/ Other)



Impervious gloves and boots. Check with protective equipment manufacturer's data.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Use NIOSH approved respiratory protection. Air-purifying respirator with combination organic vapor cartridge / particulate filter may be sufficient. Check with protective equipment manufacturer's data.

Thermal hazards

Use gloves with insulation for thermal protection, when needed.

### Environmental Exposure Controls

Do not discharge waste and/or cleaning water via public sewer system. Ensure waste is collected and contained.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Solid
Color.	Dark brown / Black
Odor	Asphalt / Bitumen / Petroleum
Odor Threshold (ppm)	Not available.
pH (Value)	Not available.
Melting Point (°C) / Freezing Point (°C)	Not available.
Boiling point/boiling range (°C):	> 371 (>700 °F)
Flash Point (°C)	> 232 (> 450 °F)
Evaporation Rate	Not available.
Flammability (solid, gas)	Not applicable.
Explosive Limit Ranges	Not applicable.
Vapor pressure (Pascal)	Not determined.
Vapor Density (Air=1)	Not determined.
Density (g/ml)	2.2 - 2.7
Solubility (Water)	Negligible
Solubility (Other)	Not known
Partition Coefficient (n-Octanol/water)	Not available.
Auto Ignition Point (°C)	Not available.
Decomposition Temperature (°C)	Not available.
Kinematic Viscosity (cSt) @ 40°C	Not available
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
<b>Other information</b>	Not available.



## COLD PATCH (CLASS 5)

### SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical stability</b>	Stable.
<b>Possibility of hazardous reactions</b>	May react violently with: Strong oxidizing agents
<b>Conditions to avoid</b>	Incompatible materials
<b>Incompatible materials</b>	Oxidizers
<b>Hazardous decomposition product(s)</b>	Combustion causes toxic fumes. Combustion products: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Sulfur oxides

### SECTION 11: TOXICOLOGICAL INFORMATION

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

#### Information on toxicological effects

Acute toxicity	LD50 (rat): >5000 mg/kg bw LD50 (dermal): >2000 mg/kg bw LC50 (inhalation, fume): >94.4 mg/m <sup>3</sup>
Irritation/Corrosivity	Causes skin irritation. May cause eye irritation. May cause respiratory irritation.
Sensitization	Not to be expected.
Repeated dose toxicity	May cause damage to organs through prolonged or repeated exposure: blood, thymus, liver, spleen, bone marrow.
Carcinogenicity	May cause cancer.

NTP	IARC	ACGIH	OSHA
Yes.*	Yes.*	Yes.*	Yes.*

Mutagenicity	Contains: Benzene (CAS# 71-43-2). See note below.
Reproductive toxicity	Not to be expected.

**Other information** \* IARC (2013, volume 103) identifies that "occupational exposures to straight-run bitumens and their emissions during road paving are possibly carcinogenic to humans (Group 2B)." However, classification as a carcinogen under OSHA 29 CFR 1910.1200 is not warranted given the absence of positive cancer findings in human epidemiological studies and in cancer studies with laboratory animals when exposed dermally or by inhalation to asphalt products or fume condensates that are typical of road paving applications. IARC (2013, volume 103) also identifies that "occupational exposures to oxidized bitumens and their emissions during roofing are probably carcinogenic to humans (Group 2A)." Roofing shingles, which are considered an article under OSHA 29 CFR 1910.1200, are sometimes recycled into road paving asphalt mix. Emissions from oxidized bitumen, e.g., from shingles, at road paving temperatures are not expected to be qualitatively different than emissions from straight-run bitumens, and therefore would not warrant a carcinogen classification under OSHA 29 CFR 1910.1200. Contains crystalline silica, an OSHA-regulated carcinogen, inherent in the aggregate. ACGIH classifies crystalline silica as a *Suspected Human Carcinogen* (A2).

**Other information** \* Contains: Benzene (CAS# 71-43-2). NTP - Known Human Carcinogen; IARC Group 1 - Known Human Carcinogen; ACGIH A1 - Confirmed Human Carcinogen; OSHA Regulated Carcinogen (29 CFR 1910.1028 and 29 CFR 1926.1128). May cause genetic defects.

### SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Short term	LL50 (48 hour): >100 mg/l (Fish) LL50 (48 hour): >100 mg/L (Aquatic Invertebrates) EL50 (48 hour): >100 mg/L (Aquatic Plants)
------------	---



## COLD PATCH (CLASS 5)

Long Term	No data
<b>Persistence and degradability</b>	The product is poorly biodegradable.
<b>Bioaccumulative potential</b>	The product has low potential for bioaccumulation.
<b>Mobility in soil</b>	The product has low mobility in soil.
<b>Results of PBT and vPvB assessment</b>	Not classified as PBT or vPvB.
<b>Other adverse effects</b>	None known.

### SECTION 13: DISPOSAL CONSIDERATIONS

<b>Waste treatment methods</b>	Disposal should be in accordance with local, state or national legislation. Consult this asphalt producer, permitted waste disposal contractor or the local authority for advice on waste disposal or recycling options.
<b>Additional Information</b>	None known.

### SECTION 14: TRANSPORT INFORMATION

**Ground or Water Domestic Voyage (DOT):** Not regulated when transported below 240°C (464 °F).

### SECTION 15: REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**TSCA (Toxic Substance Control Act) - Inventory Status:** All components listed or polymer exempt.

**RCRA Hazardous Waste Number (40 CFR 261.33):** None

**US RCRA Hazard Class:** Not applicable.

**Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):**

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	-----	-----	-----

**SARA 311/312 - Hazard Categories:**

Fire    Sudden Release    Reactivity    Immediate (acute)    Chronic (delayed)

**SARA 313 - Toxic Chemicals (40 CFR 372):**

Chemical Name	CAS No.	Typical %wt.
None	-----	-----

**SARA 302 - Extremely Hazardous Substances(40 CFR 355):**

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	-----	-----	-----

### SECTION 16: OTHER INFORMATION

**Additional Information**

**The following sections contain revisions or new statements: 1 - 16**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. The manufacturer gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. The manufacturer accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.